

CALCICHEM 110 FRF

Description

CALCICHEM 110 FRF is a mineral modifier with a high, very fine, treated CaCO_3 content that has an excellent dispersion in the final product, indicated for direct addition in the processing of PE/PP based products. The CALCICHEM 110 FRF mineral modifier is designed for films, Raffia and ropes and also suitable for general-purpose products with PE and PP carriers.

Item	unit	Typical Value
Carrier	-	polyolefine
CaCO_3 content	(%)	80 ± 2
Moisture content	(ppm)	≤ 1500
Melt Index (2.16kg/230 °C)	(g/10min)	1.5 ± 1
Density @ 23 °C	(g/cm ³)	1.86 ± 0.05

Advantage

- Increase of productivity
- Raw material costs reduction
- Thermal conductivity improvement
- Power consumption Reduction
- Print improvement on the end product
- Increase of the anti-blocking effect

Packaging

CALCICHEM 110 FRF is supplied in standard pellet form packed in 25 kg bags.

Storage and handling

CALCICHEM 110 FRF should be stored to prevent direct sunlight and heat exposure. The storage area should also be dry and preferably not exceed 50°C; Bad storage conditions may lead to quality deterioration and product performance. It is advisable to pre-dry before use and process within 18 months after production date.

Disclaimer: The information & data presented herein are typical values & should not be considered specifications and may be used as a guideline only. POLYCHEM does not undertake any responsibility for any outcome or results from adopting or replicating the data mentioned above & information thereon for possible use for various applications. POLYCHEM reserves the right to change the information & data without any prior notice or information. The user will solely be responsible for any process/product usage.

