

RAFCOLOR

❖ Description

RAFCOLOR is the white masterbatch that consists of a high proportion of rutile titanium dioxide and thermoplastic polypropylene resin. The selected titanium dioxide has good opacity and dispersion performance. Highly-concentrated white MB with excellent dispersion and thermal stability can be applied to general-purpose products. It is recommended for raffia, Tapes, CF/BCF yarn, and other products.

Item	Unit	Technical indicators
Titanium crystal type	--	Rutile type
Solid content	(%)	80 +/- 2
Moisture content	(ppm)	≤1500
Bulk density	(kg/m ³)	1050-1250
Melt Index	(g/10min)	8.00-20.00
Density	(kg/m ³)	2.0

❖ Advantage

RAFCOLOR is Featured with excellent dispersion, high compatibility, good processability, low water uptake, and stable properties.

❖ Packaging

white masterbatch RAFCOLOR is supplied in standard pellet form packed in 25 kg bags.

❖ Storage and handling

RAFCOLOR should be stored to prevent direct sunlight and/or heat exposure. The storage area should also be dry and preferably not exceed 50°C; Bad storage conditions may lead to quality deterioration and product performance. It is advisable to process PP resin within 18 months after delivery.

Disclaimer: The information & data presented herein are typical values & should not be considered specifications and may be used as a guideline only. POLYCHEM does not undertake any responsibility for any outcome or results from adopting or replicating the data mentioned above & information thereon for possible use for various applications. POLYCHEM reserves the right to change the information & data without any prior notice or information. The user will solely be responsible for any process/product usage.